

Technical Rider

The following *Technical Rider* is provided to ensure the best performance possible. For questions regarding this rider, please contact your booking agent.

Sound System:

The Sponsor and Venue should make provisions for sound to be mixed from the side of the stage, or in the middle or directly behind the audience. Mix position must not be behind glass or any other obstructive object. The audio engineer must have total access to entire system, including amplifiers and crossovers.

FOH P.A.:

1-LCR or Stereo P.A. for front of house with professional concert mains. P.A. must be capable of producing 105dB of clean, undistorted full range sound with a frequency response of 20 to 20k hertz and should include all amplifiers and cables. Subwoofers are not required, but a plus if available.

FOH Console:

An analogue or digital 24 Ch (min) mixer with 3 or 4 band semi parametric EQ, hi-pass filters, and at least 4 aux sends. Preferred mixers are Behringer x32, Midas m32, Yamaha LS9, Allen & Heath q32 or MixWizard, but we can use just about any professional mixer. If a digital mixer is provided, then there is no need for outboard eqs or effects processors. Channels must be assignable to stereo, mains, or groups.

Monitors:

Monitors will be mixed from front of house console.

8 wedge monitors - 4 in front are 1 mix run off of aux 1 with a graphic eq inline. 4 in back are individual mixes to the preference of each musician.

Monitors must be 2 way, preferably with at least a 10" speaker with 1" horn. Any monitor similar to EAW JFX 100', EAW JFX 250's, Meyer PSM-2 or EV X Array is preferred.

Power amps capable of pushing 1 discreet mix.

Microphones:

6 (4 vocal, 2 spare) SHURE or SENNHEISER WIRELESS (*Or equivalent, no Radio Shack*) UHF microphones on separate adjustable frequencies.

Beta 87, Beta 58, KSM9 or better heads on the transmitters.

Please label microphones with numbers 1 through 6.

One wired microphone at the FOH position will be needed for talkback and announcements. FOUR round base - straight mic stands with appropriate clips on stage.

Horns - 3 Clip On condenser (preferred) or Boom stand Instrument mic. SHURE SM-57 or better.

Guitar - SHURE SM-57 or better.

Bass - Direct Input 2 way

Drums - Kick - SHURE beta 52a or better. Snare / Hi-Hat - SHURE SM-57 or better.

Overhead - SHURE SM-81 or better.

FOH Rack: (if using a digital console, some of these items may not be needed)

4 (or 3 for Stereo Systems) Channels (LR or LCR, Monitor Mix 1) of 1/3 Octave Graphic EQ. 1 Digital Reverb Unit (TC Electronic, Yamaha or Lexicon)

If we use a digital console with built in effects, we can skip the above Digital Reverb Unit.

1 Digital Delay Unit (TC Electronic, Yamaha or Lexicon)

If we use a digital console with built in effects, we can skip the above Digital Delay Unit.

Etc:

All necessary patch cables will be needed including enough speaker cable for FOH and Monitors. All appropriate power, amplification, and crossovers.

Mixer Channel Input List

CH 1	RF 1		CH 13	Bass Direct Input
CH 2	RF 2		CH 14	Drums 1
CH 3	RF 3		CH 15	Drums 2
CH 4	RF 4		CH 16	Drums 3
CH 5	RF 5 (Spare)		CH 17	Horn Mic 1 - Clip On when available
CH 6	RF 6 (Spare)		CH 18	Horn Mic 2 - Clip On when available
CH 7			CH 19	Horn Mic 3 - Clip On when available
CH 8			CH 20	Digital Reverb Return L
CH 9	Talk Back		CH 21	Digital Reverb Return R
CH 10	Keys 1		CH 22	Digital Delay L
CH 11	Keys 2		CH 23	Digital Delay R
CH 12	Guitar		CH 24	Playback Device L
Aux 1	Pre – Monitors		Aux 3	Post – Digital Delay
Aux 2	Post - Digital Reverb		Aux 4	Subwoofers (if available)

Lighting:

The stage should be evenly lit all the way across and up and down stage. Lighting should be flesh-tones, blue, magenta, red, and yellow.

Staging:

Stage should have a minimum of 16' wide x 12' deep x 8" high playing space, with a minimum 8' height between the stage and ceiling, and a maximum distance of 6' between stage and closest audience member.

Stairs should lead from stage left and stage right directly into the audience.

There should be wing space or at least side panels for quick changes to be made on either side of the stage. Access to a backstage changing area will also work.

Please make sure there is plenty of bottled water set for performers for sound check and show.

Playback for Track Shows:

1 Stereo CD Player or Macintosh Computer with qLab.

Please include cables to connect playback device, whether it's the CD player or computer.

If a computer with qLab is provided, Entertainment Central can provide a USB key with the show built.

IF CLIENT IS PROVIDING BACKLINE FOR FLY DATE

The following band backline and monitoring would be needed:

5 piece drum kit:

6x14 black beauty snare drum (or equivalent) DW or Yamaha Pro drum kit:

22 kick

12 tom (rack mounted)

14 & 16 floor toms (floor legs)

Pro Cymbal package to include: 20 ride

14 HH

16 & 18 Crashes 18 China

All stands, hardware, pedals (DW 5000 or 9000), throne, backup snare drum, new drum heads (coated G2s on top, coated G1s on the bottom).

Pro bass rig:

Ampeg, Eaden or similar (1 - 15' or 2 - 10's)

Pro guitar amp:

Fender twins, Black Star or Similar

Keyboardist:

(1) Korg Kronos 61-key keyboard (or similar)

(1) Roland XP80 (or similar)

keyboards with one sustain & volume pedal.

(1) two-tier keyboard stand and all connecting cables are required also. (height of keyboard player is approx 5'10" - 6'). (1) One Roland KC500, KC550, or KC880

Keyboard Amplifier.

All cabling and stands for stage plot and the below.

Stage Plot for Band Shows (11 piece)

Stage: Approx. 30' by 20' Stage is requested. 30 inch height.

Electrical: 3- 4 way boxes at stage (20 amp, 110 volt)

